VILLAGE OF NORTHBROOK

FINAL **PLUMBING** INSPECTION - New Single-Family Construction



Key To Inspection Remarks:

(Bill Reupert, Plumbing Inspector, 847.664-4050)

Project Ade	drace		F = Failed
Project Add	dress:		NA = Not Applicable 1 = Approved During Insp. #1
Permit#:			2 = Approved During Re-Insp. #2
			3 = Approved During Re-Insp. #3
Inspection #	:1: Date: Owner/Contractor Signa	ature.	
Inspection #			
•			
Inspection #	3: Date: Owner/Contractor Signa	iture:	
PLE	ASE READ: The below code items represent primary sections,	but is <u>not</u> all ind	clusive; other components and systems will be inspected.
1.	<u>Fixtures-</u> Required fixtures for occupancy are		18"x18" if pump is located < than 24" from access
	installed [Sec. 890. Appendix A, Table B] All fixtures		opening.
	constructed of approved materials [Sec. 890.		[(NB Amended code 421.5)]
	Appendix A, Table A; 890.210], All fixtures set level	13	Sanitary Pit- Sanitary pit gas tight cover secured and
	and true [Sec. 890.630 d)], All fixtures secured [Sec.		vented [Sec. 890.1360 a)]
	890.630 b)], All fixtures installed in proper location	14	Gate/Check Valve- Gate valve and check valve installed on
	[Sec. 890.630 f)]		sanitary pump discharge
2	Water Supply - Hot, cold or tempered water supplied		[Sec. 890. Appendix J Illustrations K and L]
	to all fixtures that require hot, cold or tempered	15. <u> </u>	Proper Backflow Prevention- test reports shall be
	water [Sec. 890.630 e))		provided in confirming backflow prevention measures
3	Sewer/Water Services-Sewer and water services		[890.1130 b)]
	tied-in and operational [Sec. 890.170 - Local	16	RPZ Device- Lawn sprinkler system requires RPZ backflow
	Ordinances]		device [Sec. 890.1140 d)]
4	Bidets- Equipped with hot and cold water and an	17	<u>Threaded Valve Outlets-</u> All threaded valve outlets (hose
	atmospheric vacuum breaker (4" above overflow rim)		connections) require backflow protection
	[Sec. 890.650 i)]		[Sec. 890.1140 e) 1)]
5	Waste Disposal- Food waste disposal units trapped	18	<u>Water Supply-</u> Water supply valve or valves [Sec.
	separately [Sec. 890.710 a)]		890.1190 and [Local Ordinance amended 606.1]
6	<u>Dishwasher, discharge-</u> Dishwasher shall not	19	<u>Dead- Ends-</u> Prohibited dead ends - Water System [Sec
	discharge into food waste disposal units [Sec.		890.1200 c) - Waste & Vent [Sec. 890.1320 d)]
	890.710 a)]	20	Water Distribution Sys Correct size of water distribution
	<u>Dishwasher, drain-</u> Dishwashing machine drain		system [Sec. 890.1210 b)]
	carried to underside of counter top [Sec. 890.770 a)]	21	
	<u>Dishwasher, trap-</u> Dishwashing machine drain		water quality [Sec. 890.1230 d) 3)]
	separately discharged to trap or tailpiece [Sec.	22	
	890.770 a)]		drain, service sink, sump, or trapped and vented P-trap in
	<u>Temperature-</u> Showers and shower/bath		the same room [Sec. 890.1230 d) 4)]
	combinations require automatic safety mixing device	23	
	set at a maximum of 115° at time of installation[Sec.		water heaters or storage tanks. [Sec. 890.1230 f)]
	890.690 b)]	24	
	<u>Hand Held</u> - Hand-held shower backflow protection		[Sec. 890.1600 a & b) Appendix K - Illustration GG]
	on tub or shower [Sec. 890.1130 f)]	25	· · · · · · · · · · · · · · · · · · ·
	Whirlpool Pump- Whirlpool pump located above trap		according to Public Work Dept. requirements
	weir [Sec. 890.750 a)]	26	Waste & Vent- Sump pump air gap according to standard
	Whirlpool Pump, access- Whirlpool pump access		detail [(Northbrook Engineering Specifications)]
Comments:	Mininum size manufacture spec's or 12"x12" or		
<u>comments.</u>			
кесоттепс	d for Occupancy Certificate: 🛮 Temporary Certificate Date:_		